



Tabletop Transient Absorption Spectroscopy System



HARPIA-LIGHT transient absorption spectroscopy system combines accessibility, versatility, and unparalleled performance in a single-box design. Based on advanced femtosecond laser technology, it allows precise and accurate measurement and analysis of transient events on a femto-to-nanosecond time scale.

HARPIA-LIGHT excels in providing exceptional measurement sensitivity, high temporal resolution, and broad spectral coverage. Despite its compact size, HARPIA-LIGHT houses an industrial-grade femtosecond laser and a spectrograph with advanced, yet user-friendly data acquisition software. The intuitive interface and streamlined workflow enable seamless

operation, saving valuable time and effort. By simply placing the sample and clicking a button, instant access to a wealth of information is achieved. Moreover, HARPIA-LIGHT features flexible polarization control, a 7.5 ns delay line, and advanced analysis algorithms, providing extensive options for further data assessment.






Specifications

Modes	Transmission and reflection
Probe spectral range	460 – 910 nm
Probe polarization control	Linear (0 - 180°)
Pump wavelengths	515 nm, 343 nm
Delay range (resolution)	7.5 ns (10 fs)
Temporal resolution	≤ 290 fs
Laser repetition rate	60 kHz, any fundamental repetition rate division
Maximum data acquisition rate	3850 Hz
DIMENSIONS	
Physical dimensions (L × W × H)	870.5 x 388 x 346 mm



Front view

Measurements



Spectral dynamics of DCM laser dye in solution acquired using **HARPIA-LIGHT**.

MEASUREMENT CONDITIONS

Pulse repetition rate: 60 kHz Pump wavelength: 343 nm Acquisition time: 3 s per spectrum (per delay point)

Processes explored by ultrafast spectroscopy

- Electron and proton transfer
- Solvation
- Vibrational relaxation
- Exciton energy transfer
- Photoreaction dynamics

Drawing

